

Super Farm Tractor Rules

(All general rules apply)
9300 pound class

- Must follow contest rules.
- Maximum cubic inch 640.
- Only farm tractors with rubber tires. No duals, 4WD's, chains, etc. Cut tires allowed.
- No nitrous or propane.
- Hitching point to be a minimum of 20" from center of axle and a maximum of 20" high. Drivers must furnish a clevis or hitch point with at least 3.5 inch hole.
- No portion of tractor may interfere with sled or hitching the sled.
- Weights must be secured. Loss of weights will lead to immediate disqualification. No weights shall extend more than 12" from the tire. No protruding bolts will be allowed anywhere. No weight frame or weights may extend 24" beyond forward point of tractor.
- Tractors must have a hood and grill and have working brakes.
- All tractors must have kill switches and wheelie bars.
- One adequately shielded turbocharger allowed. Exhaust housing and exhaust manifold bolt pattern no larger than 2.75 x 3.5 inches.
- All turbocharged tractors must have 2 – 3/8" grade 5 bolts perpendicular to each other and a maximum of 1" apart.
- Must be stock block, stock head, stock exhaust manifold with no visual modifications.
- All operators must wear helmets and firesuits.
- All tractors must have straight vertical stack or factory exhaust.
- All tractors must have fire extinguishers mounted with easy access to driver.
- Front wheels off the ground 25" will be deemed unsafe by judges.
- Exhaust: All air must exit through a 3" opening.
- Must have clutch blanket.
- Must have engine side shields that are solid (.125 aluminum or .90 steel).
- No component chassis.
- Tie bars are mandatory or full frame must be mounted rigid to engine, transmission, and final drive housing.
- Largest fuel injection pump will be a P-pump original equipment housing with only one plunger per cylinder.
- Roll cage and seat belts are required.